



AiV-CDD62S

- Sensor: SONY 1/3" CCD
- Resolution: 600TVL
- Lens: 2.8 mm
- IR distance: 20 m
- Aviation connector: 4P / BNC
- Minimum illumination: 0.001 lx
- Weatherproof: IP67

Model	AiV-CDD62S
Image sensor	SONY 1/3" CCD
Resolution	600TVL
Minimum illumination	0.001 lx, (F1.2, AGC ON), 0 lx with IR
Signal system	PAL/NTSC (optional)
Shutter speed	from 1/50 s to 1/100000 s
Lens	2.8 mm, F2.0
FOV	Horizontal: 0°-355°; vertical: 0°-90°; rotation: 0°-355°
Day and night mode	Auto
Synchronization system	Inter-sync
Video output	1 Vp-p composite output (75Ω/BNC) (75Ω/BNC and aviation connector optional)
SN	> 62 dB
Audio	-
ONVIF	-
Color	Black/white (optional)
IR distance	20 m
Input voltage	DC 12V ±10%
Power consumption	< 5W
Video output cable length	40 cm
Weatherproof	IP67
Operation temperature	from -65° to +65°C
Operation humidity	< 90% RH (non-condensation)
Selection guide	A: SONY CCD, B: SHARP, CDD C:CMOS
Dimensions	80 mm (L) x 77 mm (W) x 70 mm (H)
Net / Gross weight	283 g / 322 g