



## AiV-CDD72S

- Sensor: SONY 1/3" CCD
- Resolution: 700TVL
- Lens: 2.8 mm
- IR distance: 20 m
- Aviation connector: 4P / BNC
- Minimum illumination: 0.001 lx
- Weatherproof: IP67

|                           |   |
|---------------------------|---|
| Model                     | AiV-CDD72S  |
| Image sensor              | SONY 1/3" CCD   |
| Resolution                | 700TVL  |
| Minimum illumination      | 0.001 lx, (F1.2, AGC ON), 0 lx with IR                                      |
| Signal system             | PAL/NTSC (optional)   |
| Shutter speed             | from 1/50 s to 1/100000 s   |
| Lens                      | 2.8 mm, F2.0  |
| FOV                       | Horizontal: 0°-355°; vertical: 0°-90°; rotation: 0°-355°                    |
| Day and night mode        | Auto  |
| Synchronization system    | Inter-sync  |
| Video output              | 1 Vp-p composite output (75Ω/BNC) (75Ω/BNC and aviation connector optional) |
| SN                        | > 62 dB   |
| Audio                     | -   |
| ONVIF                     | -   |
| Color                     | Black/white (optional)  |
| IR distance               | 20 m  |
| Input voltage             | DC 12V ±10%   |
| Power consumption         | < 5W  |
| Video output cable length | 40 cm   |
| Weatherproof              | IP67  |
| Operation temperature     | from -65° to +65°C  |
| Operation humidity        | < 90% RH (non-condensation)   |
| Selection guide           | A: SONY CCD, B: SHARP, CDD C:CMOS   |
| Dimensions                | 80 mm (L) x 77 mm (W) x 70 mm (H)   |
| Net / Gross weight        | 283 g / 322 g   |