



- Sensor: 1/4" CMOS
- Resolution: 720P
- Lens: 2.8 mm
- IR distance: 20 m
- Aviation connector: 6P / RJ 45
- Minimum illumination: 0.01 lx, F1.2
- ONVIF: yes
- at p oo : P67

AIV-C N12S

| | |
|---------------------------|--|
| Model | AIV-C N12S |
| Image sensor | 1/4" CMOS |
| Resolution | 720P |
| Minimum illumination | 0.01 lx, (F1.2, AGC ON), 0 lx with IR |
| Signal system | PAL/NTSC (optional) |
| Shutter speed | from 1/50 s to 1/100000 s |
| Lens | 2.8 mm, F2.0 |
| FOV | Horizontal: 0°-355°; vertical: 0°-90°; rotation: 0°-355° |
| Day and night mode | Auto |
| Synchronization system | Inter-sync |
| Video output | 1 CH, ONVIF protocol (RJ45 and 6 pins aviation optional) |
| Video compressed | 32 Kbps - 8 Mbps |
| SN | > 52 dB |
| Protocols | RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/ONVIF |
| Audio | - |
| ONVIF | yes |
| Color | Black/white (optional) |
| IR distance | 20 m |
| Input voltage | DC 12V ±10% |
| Power consumption | < 5W |
| Video output cable length | 40 cm |
| Weatherproof | IP67 |
| Operation temperature | from -65° to +65°C |
| Operation humidity | < 90% RH (non-condensation) |
| Selection guide | A: SONY CCD, B: SHARP, CDD C: CMOS |
| Dimensions | 80 mm (L) x 77 mm (W) x 70 mm (H) |
| Net / Gross weight | 340 g / 341 g |